

 class 1
  class 2
  class 3

$h_i^{(k+1)}$


by definition of desirable one-hop m2m (taking sum pooling as  $\phi(\cdot)$ )

base case:



$$h_i^{(k+1)} = \left[ h_{N_1(i)}^{(k+1)} \parallel h_{N_2(i)}^{(k+1)} \parallel h_{N_3(i)}^{(k+1)} \right] \quad h_{N_t(i)}^{(k+1)} = \sum_{v_j \in N(v_i)} h_j^{(k)} \quad N_t(i) = \{v_j \mid v_j \in N(v_i), y_j = t\}$$

Assumption:



$$h_j^{(k+d)} = \left[ h_{N_1^d(j)}^{(k+d)} \parallel h_{N_2^d(j)}^{(k+d)} \parallel \dots \parallel h_{N_{3^d}^d(j)}^{(k+d)} \right]$$

$$h_{N_t^d(j)}^{(k+d)} = \sum_{v_{j'} \in N_t^d(j)} h_{j'}^{(k)}$$

$$N_t^d(j) = \{v_{j'} \mid \text{dis}(v_j, v_{j'}) = d, y_{j'} = (t+2)\%3 + 1\}$$

by definition of desirable one-hop m2m


induction step:

$$h_i^{(k+d+1)} = \left[ h_{N_1(i)}^{(k+d+1)} \parallel h_{N_2(i)}^{(k+d+1)} \parallel h_{N_3(i)}^{(k+d+1)} \right]$$

$$h_{N_t(i)}^{(k+d+1)} = \sum_{v_j \in N(v_i)} h_j^{(k+d)}$$

$$N_t(i) = \{v_j \mid v_j \in N(v_i), y_j = t\}$$

Therefore,  $h_i^{(k+d+1)}$



$$h_i^{(k+d+1)} = \left[ h_{N_1^{d+1}(i)}^{(k+d+1)} \parallel h_{N_2^{d+1}(i)}^{(k+d+1)} \parallel \dots \parallel h_{N_{3^{d+1}}^{d+1}(i)}^{(k+d+1)} \right]$$

$$h_{N_t^{d+1}(i)}^{(k+d+1)} = \sum_{v_j \in N_t^{d+1}(i)} h_j^{(k)}$$

$N_t^{d+1}(i) = \{v_j \mid \text{dis}(v_i, v_j) = d+1, y_j = (t+2)\%3 + 1\} \longrightarrow$  There are no heterophilic nodes within the same chunk.