

```

from math import log2, ceil, floor
import numpy as np

```

```

def sh(bandit: BanditProblem, n: int, T: int) -> int:
    L = _get_target_pulls(n, T)                # L: target pulls
    N = np.append(np.zeros(n, dtype=int), -1e9) # N: pull counts
    R = np.append(np.zeros(n, dtype=float), 0.) # R: avg rewards
    for t in range(T):
        a = np.argmax(np.where(N == L[t], R, -np.inf))
        r = bandit.pull(a)
        R[a] = (R[a] * N[a] + r) / (N[a] + 1)
        N[a] += 1
    return int(np.argmax(np.where(N >= max(N), R, -np.inf)))

```

```

def ash(bandit: BanditProblem, n: int, B: int, b: int = 1) -> int:
    L = _get_target_pulls(n, b * B)                # L: target pulls
    N = np.append(np.zeros(n, dtype=int), -1e9) # N: pull counts
    R = np.append(np.zeros(n, dtype=float), 0.) # R: avg rewards
    for i in range(B):
        batch = []
        M = np.zeros_like(N)                        # M: virtual pull counts
        for j in range(b):
            t = i * b + j
            N_max = np.max(np.where(N + M == L[t], N, -np.inf))
            a = np.argmax(np.where((N + M == L[t]) & (N == N_max), R, -np.inf))
            batch.append(a)
            M[a] += 1
        rewards = bandit.batch_pull(batch)
        for a, r in zip(batch, rewards):
            R[a] = (R[a] * N[a] + r) / (N[a] + 1)
            N[a] += 1
    return int(np.argmax(np.where(N >= max(N), R, -np.inf)))

```

```

def _get_target_pulls(n: int, T: int) -> list[int]: # advance-first
    target_pulls = []
    num_rounds = ceil(log2(n))
    num_active_arms = n
    cum_pulls = 0
    for r in range(num_rounds):
        J = floor(T / (num_active_arms * num_rounds))
        if r == num_rounds - 1:
            remaining_pulls = T - len(target_pulls)
            J = remaining_pulls // 2
        for _ in range(num_active_arms):
            for i in range(J):
                target_pulls.append(cum_pulls + i)
            cum_pulls += J
        num_active_arms = ceil(num_active_arms / 2) # halving
    return target_pulls + [int(-1e9)] * (T - len(target_pulls))

```