

1. Sample trajectories

(Unstack b3 b2)
(Put-down xqb2)
(Unstack b2 b5)
(Put-down b3)
(Stack b5 b2)
...

2. Execute actions

Time step 1: (Unstack b3 b2)
Adding (holding b3)
Deleting (on b3 b2)

Time step 2: (Put-down b2)
Plan failed: unsatisfied precondition
Plan repair: (Set (holding b2) to true)

3. Predict action semantics

Preconditions of "Put-down ?ob":
(holding ?ob), (not (on-table ?ob))

Postconditions of "Put-down ?ob":
(on-table ?ob), (clear ?ob), (arm-empty)
...

Learned action semantics

Put-down Preconditions: [
(holding ?ob): 1.0
(not (on-table ?ob)): 0.3
]

Put-down Postconditions: [
(arm-empty): 1.0
(on-table ?ob): 0.8
(clear ?ob): 0.6
]

Unstack Preconditions: [
...
]

Provided Info

Domain Info

- Domain desp
- Type
- Predicate
- Action desp

Problem Info

- Task desp
- Problem file


Derived Info

Memory Info

- Failed trajs
- Sampled dynamics model

Solver Info

- Candidate trajs



4. Sample preconditions and postconditions

Put-down Preconditions:
(holding ?ob)

Put-down Postconditions:
(on-table ?ob)
(arm-empty)

Unstack Preconditions:
...