

You are a robot with a gripper that can move objects between different rooms.

The environment is defined with the Planning Domain Definition Language (PDDL) as

PDDL Types:

room object robot gripper

PDDL Predicates:

(at-robby ?r - robot ?x - room)

(at ?o - object ?x - room)

(free ?r - robot ?g - gripper)

(carry ?r - robot ?o - object ?g - gripper)

Here are the actions you can perform in the environment:

Move from one room to another: move (?r - robot ?from ?to - room). The effects are (at-robby ?r ?to), (not (at-robby ?r ?from)).

Pick up an object using the gripper: pick (?r - robot ?obj - object ?room - room ?g - gripper). The preconditions are (at-robby ?r ?room), (at ?obj ?room), (free ?r ?g). The effects are (not (free ?r ?g)), (not (at ?obj ?room)), (carry ?r ?obj ?g).

Drop an object that it is carrying: drop (?r - robot ?obj - object ?room - room ?g - gripper). The preconditions are (carry ?r ?obj ?g). The effects are (at ?obj ?room), (free ?r ?g), (not (carry ?r ?obj ?g)).

An example planning problem is:

You control 2 robots, each robot has a left gripper and a right gripper.

There are 4 rooms and 6 balls.

robot2 is in room3. robot1 is in room2.

ball1 is in room3. ball2 is in room1. ball3 is in room3. ball4 is in room2. ball5 is in room4. ball6 is in room4.

The robots' grippers are free.

Your goal is to transport the balls to their destinations.

ball1 should be in room4.

ball2 should be in room1.

ball3 should be in room1.

ball4 should be in room2.

ball5 should be in room1.

ball6 should be in room1.

which means the initial state is:

((at-robby robot1 room2)

(free robot1 rgripper1)

(free robot1 lgripper1)

(at-robby robot2 room3)

(free robot2 rgripper2)

(free robot2 lgripper2)

(at ball1 room3)

(at ball2 room1)

(at ball3 room3)

(at ball4 room2)

(at ball5 room4)

(at ball6 room4))

A plan for the example problem is:

(pick robot2 ball1 room3 lgripper2)

(pick robot2 ball3 room3 rgripper2)

(move robot2 room3 room1)

(drop robot2 ball3 room1 rgripper2)

(move robot2 room1 room4)

(pick robot2 ball5 room4 rgripper2)

(drop robot2 ball1 room4 lgripper2)

(pick robot2 ball6 room4 lgripper2)

(move robot2 room4 room1)

(drop robot2 ball6 room1 lgripper2)

(drop robot2 ball5 room1 rgripper2)

Now I have a new planning problem and its description. Can you provide a executable plan, in the way of a sequence of behaviors, to solve the problem?

The new planning problem is:

You control 2 robots, each robot has a left gripper and a right gripper.

There are 3 rooms and 4 balls.

robot2 is in room3. robot1 is in room2.

ball1 is in room3. ball2 is in room1. ball4 is in room3. ball3 is in room1.

The robots' grippers are free.

Your goal is to transport the balls to their destinations.

ball1 should be in room2.

ball2 should be in room2.

ball3 should be in room3.

ball4 should be in room3.

which means the initial state is:

((at-robby robot1 room2)

(free robot1 rgripper1)

(free robot1 lgripper1)

(at-robby robot2 room3)

(free robot2 rgripper2)

(free robot2 lgripper2)

(at ball1 room3)

(at ball2 room1)

(at ball3 room1)

(at ball4 room3))