





Method	Rotary Position Embedding(RoPE)	Chunk Position Encoding(CPE)
Schematic Drawing	 <p>Diagram illustrating the schematic drawing of RoPE. At the top, a sequence of 16 white squares represents tokens. Below it is a circle with a radius labeled θ from the x-axis. A green horizontal bar at the bottom shows indices from 0 to 15.</p>	 <p>Diagram illustrating the schematic drawing of CPE. At the top, a sequence of 16 white squares represents tokens. In the middle, a 3D sphere has a vector $\phi\rangle$ at an angle θ from the z-axis and φ from the x-axis. Below it is a color-coded horizontal bar showing indices from 0 to 15 mapped to colors (green, yellow, magenta, blue).</p>
Equation	$f_{\{q,k\}}(\mathbf{h}, m) = e^{im\theta} h$	$f_{\{q,k\}}(\mathbf{h}, m, j) = e^{im\theta} (\cos \varphi_j \mathbf{h}^\perp + \sin \varphi_j \mathbf{h})$
Long-term Decay	 <p>Plot showing the long-term decay of the upper bound. The y-axis is labeled "Upper Bound" and ranges from 5 to 30. The x-axis is labeled "$m-n$" and ranges from 0 to 4000. The curve starts at approximately 32 and decays rapidly, reaching a stable oscillatory state around a value of 10 after $m-n \approx 1000$.</p>	 <p>3D surface plot showing the upper bound as a function of $m-n$ and $\phi_i - \phi_j$. The vertical axis is labeled "Upper Bound" and ranges from 0 to 30. The horizontal axis is labeled "$m-n$" and ranges from 0 to 1000. The depth axis is labeled "$\phi_i - \phi_j$" and ranges from 0 to 4. The surface shows a sharp peak at low $m-n$ and low $\phi_i - \phi_j$, with the upper bound decreasing as both parameters increase.</p>
Position Resolution	$\varepsilon_{rope} = 1 \xrightarrow{\text{PI}} \varepsilon'_{rope} = \frac{L_p}{L}$	$\varepsilon_{cpe} = 1 \xrightarrow{\text{PI}} \varepsilon'_{cpe} > \frac{L_p}{L}$