

Question 1: I have an orange, five raspberries, two books, three plums, a pencil, and a grape. How many fruits do I have?

CoT with Natural Language:

Let's think step by step.

We first identify the fruits on the list and include their quantity in parentheses: orange (1), raspberries (5), plums (3), grape (1).

Now, let's add the numbers in parentheses: $1 + 5 + 3 + 1 = 10$. So the answer is 10.

AoT with Natural Language:

Step 1: Identify fruits from all items.

Of all the items, the orange, raspberry, plum, and grape are fruits.

Step 2: Identify the number of each fruit.

There are 1 orange, 5 raspberries, 3 plums, and 1 grape.

Step 3: Sum the number of fruits.

There are $1 + 5 + 3 + 1 = 10$ fruits in total.

Therefore, the answer is $\boxed{10}$

a_1^1
 a_1^2
 a_1^1
 a_2^2
 a_3^1
 a_3^2

Question 2: Given an $N \times N$ maze that contains one start point S, one end point E, several empty spaces 0, and several walls 1. The player can move up, down, left, and right, but cannot pass through walls. Find the shortest path length from the start to the end. If the end is unreachable, output -1. Example of the given maze: maze=[['S', 0, 0], [1, 1, 0], [0, 0, 'E']]

CoT with Programming Language:

```
directions = [(0, 1), (1, 0), (0, -1), (-1, 0)]
start, end = None, None
for i in range(len(maze)):
    for j in range(len(maze)):
        if maze[i][j] == 'S':
            start = (i, j)
        elif maze[i][j] == 'E':
            end = (i, j)
```

```
queue = deque([(start, 0)])
visited = set([start])
while queue:
    (x, y), step = queue.popleft()
    if (x, y) == end:
        print(step)
        break
    for dx, dy in directions:
        nx, ny = x + dx, y + dy
        if (0 <= nx < len(maze) and
            0 <= ny < len(maze) and
            maze[nx][ny] != 1 and
            (nx, ny) not in visited):
            queue.append((nx, ny), step + 1)
            visited.add((nx, ny))
else:
    print(-1)
```

AoT with Programming Language:

```
def find_start_end(maze):
    """
    Find the start ('S') and end ('E') in the 2D-maze.
    """
    start, end = None, None
    for i in range(len(maze)):
        ...
    return start, end

def bfs(maze, start, end):
    """
    Performs a breadth-first search (bfs) on the 2D-maze
    to find the shortest path length from start to end.
    """
    queue = deque([(start, 0)])
    visited = set([start])
    while queue:
        ...
    return -1

def main(maze):
    """
    Calls other functions to answer the question.
    """
    start, end = find_start_end(maze)
    shortest_path_length = bfs(maze, start, end)
    print(shortest_path_length)
```

a_1^1
 a_1^2
 a_2^1
 a_2^2
 a_3^1