

```

36      36      #ifdef WITH_SSH1
37      37
38      38      static int ssh_auth_status_termination(void *s){
39      39          ssh_session session=s;
40      40          if(session->auth_state != SSH_AUTH_STATE_NONE ||
41      41              session->session_state == SSH_SESSION_STATE_ERROR)
42      42          return 1;
43      43          return 0;
44      44      }
45      45
46      46      static int wait_auth1_status(ssh_session session) {
47      -     enter_function();
48      47      /* wait for a packet */
49      48      if (ssh_handle_packets_termination(session,SSH_TIMEOUT_USER,
50      49          ssh_auth_status_termination, session) != SSH_OK){
51      -     leave_function();
50      +     return SSH_AUTH_ERROR;
52      51      }
53      52      }
54      53      SSH_LOG(SSH_LOG_PROTOCOL,"Auth state : %d",session->auth_state);
55      -     leave_function();
54      +     
```

■ ■ ■

```

230      -     leave_function();
224      +     return rc;
231      225      }
232      226      }
233      227      }
234      228      #endif /* WITH_SSH1 */
235      229      /* vim: set ts=2 sw=2 et cindent: */ 
```

■ ■ ■

```

269      265      #ifdef WITH_SERVER
270      266      int crypt_set_algorithms_server(ssh_session session){
271      267          char *method = NULL;
272      268          int i = 0;
273      -         int rc = SSH_ERROR;
274      269          struct ssh_cipher_struct *ssh_ciphertab=ssh_get_ciphertab();
275      270
276      271          if (session == NULL) {
277      272              return SSH_ERROR;
278      273          }
279      274
280      -         /* we must scan the kex entries to find crypto algorithms and set their
281      -         enter_function(); 
```

■ ■ ■

```

338      -         rc = SSH_OK;
339      -         error:
340      -         leave_function();
341      -         return rc;
335      +         return SSH_OK;
336      +         }
337      338      #endif /* WITH_SERVER */
338
339
340
341
342
343
344
... 
```